



SPLINE INFO: D 32/64 PITCH 26 TEETH PRESSURE ANGLE: 30.0° ARC TOOTH THICKNESS: 0.0441" +0/-0.002" **ROOT DIA: 0.762"** PITCH DIA: 0.8125" OUTSIDE DIA: 0.844 +0/-0.005" BASE CIRCLE DIA: 0.7036 DIMENSION OVER TWO 0.0540" DIA PINS: 0.8805 +0/-0.0033 $\phi_{0.895}^{0.897}$ Ę 0.88 $\phi_{0.735}^{0.745}$ SYM С → 0.25 R0.008 MAX 0.03 X 45.0° CMF-R0.02 -3 PL -0.03 X 45.0° CMF Œ Ø 0.454 0.452 Ø 0.680 0.675 \emptyset 0.875 \emptyset 1.25 SYM В -R0.04 - 0.42 --- 0.70 **RB6872533-2 WRENCH** 1.42 **SECTION B-B** NOTES: 1) MATERIAL: O1 2) HEAT TREAT: 48-52 Rc **DESIGN** DART AEROSPACE LTD VM 3) FINISH: N/A 4) TOLERANCES: X.X = +/- 0.1" / +/- 1° X.XX = +/- 0.01" / +/- 0.5° X.XXX = +/- 0.005" / +/- 0.1° X.XXXX = +/- 0.0005" / +/- 0.05° DRAWN HAWKESBURY, ONTARIO, CANADA CHECKED TOOL PART # ML REV. B RB6872533 MFG. APPR. SHEET 3 OF 3 PARALLELISM, ECCENTRICITY AND SYMMETRY ABOUT ALL CENTER LINES = +/-0.005" **APPROVED** WRENCH AND HOLDER INST/REM COMPRESSOR TIE BOLT NTS 5) UNITS: INCHES UNLESS OTHERWISE NOTED 6) REMOVE ALL SHARP EDGES AND BURRS DATE 2019-07-10 COPYRIGHT © 2019 BY DART AEROSPACE LTD 7) IDENTIFICATION: N/A THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT 7 5